

SAFETY DATA SHEET

GHS
United States

Section 1. Product and company identification

Product name	ETHYL TELLURAC® PDR	<u>In case of emergency</u>
Code	39507	1-203-853-1400
Supplier/Manufacturer	Vanderbilt Chemicals, LLC 30 Winfield Street Norwalk, CT 06855	Chemtrec: 1-800-424-9300 Outside US: +1-703-527-3887
Chemical name	Tellurium, tetrakis(N,N-diethylcarbamo-dithioato-kS,kS')-, (DD-8-111"1"1'1'1"1")-	
Synonym	Tellurium diethyldithiocarbamate	
Material uses	Accelerator.	
Product type	Powder.	

Section 2. Hazards identification

OSHA/HCS status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	COMBUSTIBLE DUSTS
<u>GHS label elements</u>	
Signal word	Warning
Hazard statements	May form combustible dust concentrations in air.
<u>Precautionary statements</u>	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Supplemental label elements	Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.
Hazards not otherwise classified	None known.

Section 3. Composition/information on ingredients

Substance/mixture Substance

Ingredient name	CAS number	% by weight
tellurium diethyldithiocarbamate	20941-65-5	>90.5

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	No known significant effects or critical hazards.
Ingestion	No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact	Adverse symptoms may include the following: irritation redness
Inhalation	Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	No specific data.
Ingestion	No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	In case of fire, use water spray (fog), foam, dry chemical or CO ₂ .
Unsuitable extinguishing media	Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

Specific hazards arising from the chemical

Hazardous thermal decomposition products	May form explosible dust-air mixture if dispersed. Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides
---	--

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Remark(s)

Dust suspended in air in critical proportions and in the presence of an ignition source presents an explosion hazard. As with any dry material, pouring or allowing to free-fall or to be conveyed through chutes or pipes can accumulate and generate electrostatic sparks, potentially causing ignition of the material itself, or of any flammable materials which may come in contact with the material or its container.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 6. Accidental release measures

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
tellurium diethyldithiocarbamate	<p>ACGIH TLV (United States, 6/2013). Notes: as Te TWA: 0.1 mg/m³, (as Te) 8 hours.</p> <p>OSHA PEL (United States, 2/2013). Notes: as Te TWA: 0.1 mg/m³, (as Te) 8 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). Notes: as Te TWA: 0.1 mg/m³, (as Te) 8 hours.</p> <p>NIOSH REL (United States, 10/2013). TWA: 0.1 mg/m³, (as Te) 10 hours.</p>

Appropriate engineering controls

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Section 8. Exposure controls/personal protection

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles. Recommended: splash goggles

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: lab coat


Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Dust respirator.

Personal protective equipment (Pictograms)



Section 9. Physical and chemical properties

Appearance

Physical state	Solid. [Powder.]
Color	Yellow or saffron yellow.
Odor	Odorless.
Odor threshold	Not available.
pH	Not available.
Melting point	108 to 118°C (226.4 to 244.4°F)
Boiling point	Not available.
Flash point	Not applicable.
Burning time	Not available.
Burning rate	Not available.
Evaporation rate	Not available.

Section 9. Physical and chemical properties

Flammability (solid, gas)	Not available.
Lower and upper explosive (flammable) limits	Not applicable.
Vapor pressure	Not available.
Vapor density	Not applicable.
Density	1.44 g/cm ³
Relative density	1.44
Solubility	Insoluble in the following materials: cold water.
Solubility in water	Not available.
Partition coefficient: n-octanol/water	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not available.
SADT	Not available.
Viscosity	Not applicable.

Section 10. Stability and reactivity

Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
tellurium diethyldithiocarbamate	LC50 Inhalation Dusts and mists	Rat	>0.51 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

Section 11. Toxicological information

Conclusion/Summary

There were no deaths following a 4-hour exposure of tellurium diethyldithiocarbamate at a mean concentration of 0.51 mg/L of air. This was the highest attainable concentration for the equipment used in the experimentation. The LC50 (4-hour) for tellurium diethyldithiocarbamate in rats is therefore in excess of 0.51 mg/L of air.

Irritation/Corrosion

Not available.

Conclusion/Summary

Skin

Tellurium diethyldithiocarbamate: Non-irritating to the skin. (Rabbit)

Eyes

Tellurium diethyldithiocarbamate: May cause eye irritation. (Rabbit)

Sensitization

Product/ingredient name	Route of exposure	Species	Result
tellurium diethyldithiocarbamate	skin	Guinea pig	Not sensitizing

Mutagenicity

Product/ingredient name	Test	Experiment	Result
tellurium diethyldithiocarbamate	-	Subject: Bacteria	Negative

Carcinogenicity

Not available.

Product/ingredient name	OSHA	IARC	NTP
tellurium diethyldithiocarbamate	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Section 11. Toxicological information

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Inhalation, Eyes.

Potential acute health effects

Eye contact	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	May be harmful in contact with skin.
Ingestion	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	Adverse symptoms may include the following: irritation redness
Inhalation	Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	No specific data.
Ingestion	No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

Long term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

Potential chronic health effects

Not available.

Conclusion/Summary

Overexposure may cause garlic odor of breath and sweat. Possible symptoms are somnolence, anorexia and nausea.

Overexposure to tellurium (as Te) can cause CNS effects which include headache, fatigue and weakness.

General

Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Dermal	2735.08 mg/kg

Section 11. Toxicological information

Other information

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
tellurium diethyldithiocarbamate	Acute EC50 0.064 mg/l	Daphnia	48 hours
	Acute EC50 0.034 mg/l	Daphnia	72 hours
	Acute LC50 0.344 mg/l	Fish	96 hours
	Acute NOEC 1000 mg/l	Micro-organism	3 hours

Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
tellurium diethyldithiocarbamate	OECD 301B	6 % - Not readily - 28 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
tellurium diethyldithiocarbamate	-	-	Not readily

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (K_{oc})

Not available.

Other adverse effects

No known significant effects or critical hazards.











Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (tellurium diethyldithiocarbamate)	9	III	 	Remarks Marine pollutant
TDG Classification	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (tellurium diethyldithiocarbamate)	9	III	 	Remarks Marine pollutant
ADR/RID Class	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (tellurium diethyldithiocarbamate)	9	III	 	Remarks Marine pollutant
IMDG Class	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (tellurium diethyldithiocarbamate)	9	III	 	Remarks Marine pollutant
IATA-DGR Class	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (tellurium diethyldithiocarbamate)	9	III	 	-

PG* : Packing group

Section 15. Regulatory information

[United States Inventory \(TSCA 8b\)](#) All components are active or exempted.

[U.S. Federal regulations](#)

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

[SARA 302/304](#)

[Composition/information on ingredients](#)

No products were found.

Section 15. Regulatory information

[SARA 304 RQ](#) Not applicable.

[SARA 311/312](#)

Classification COMBUSTIBLE DUSTS

[Composition/information on ingredients](#)

No products were found.

[State regulations](#)

Massachusetts None of the components are listed.

New York None of the components are listed.

New Jersey None of the components are listed.

Pennsylvania None of the components are listed.

California Prop. 65 None of the components are listed.

[International regulations](#)

Australia Inventory (AIRC) All components are listed or exempted.

Canada Inventory All components are listed or exempted.

China Inventory (IECSC) All components are listed or exempted.

Europe inventory All components are listed or exempted.

Japan Inventory (CSCL) All components are listed or exempted.

Korea inventory (KECI) All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC) All components are listed or exempted.

Philippines Inventory (PICCS) All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI) All components are listed or exempted.

Section 16. Other information

[Hazardous Material Identification System \(U.S.A.\)](#)

Health	*	1
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

[National Fire Protection Association \(U.S.A.\)](#)

Section 16. Other information



Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of printing	10/21/2022
Validation date	10/21/2022
Date of previous issue	1/19/2022
Version	4

Key to abbreviations

ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 UN = United Nations

References

Not available.

Information contact

Vanderbilt Global Services, LLC
Corporate Risk Management
1-203-295-2143

Visit www.vanderbiltchemicals.com for more information.

Notice to reader

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.