

TPS™ 20

1. PRODUCT AND COMPANY IDENTIFICATION

Company

Arkema Inc. 900 First Avenue

King of Prussia, Pennsylvania 19406

Thio and Fine Chemicals

Customer Service Telephone Number: (800) 628-4453

(Monday through Friday, 8:00 AM to 5:00 PM EST)

Emergency Information

Transportation: CHEMTREC: (800) 424-9300

(24 hrs., 7 days a week)

Medical: Rocky Mountain Poison Center: (866) 767-5089

(24 hrs., 7 days a week)

Product Information

Product name:TPS™ 20Synonyms:PolysulfideMolecular formula:(t-C12H25)2SxChemical family:Polysulfide

Product use: Additive in lubricants and greases, hydraulic fluids, heat transfer fluids,

metal working fluids.

SECTION 2: HAZARDS IDENTIFICATION

Emergency Overview

Color: colorless to light yellow

Physical state: liquid
Odor: Slightly acrid

*Classification of the substance or mixture:

Skin sensitisation, Category 1, H317

*For the full text of the H-Statements mentioned in this Section, see Section 16.



TPS™ 20

GHS-Labelling

Hazard pictograms:



Signal word: Warning

Hazard statements:

H317: May cause an allergic skin reaction.

Precautionary statements:

Prevention:

P261 : Avoid breathing mist.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves.

Response:

P302 + P352 : IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 : If skin irritation or rash occurs: Get medical advice/ attention.

P363: Wash contaminated clothing before reuse.

Disposal:

P501: Dispose of contents or container to an approved waste disposal plant.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Wt/Wt	GHS Classification**
Polysulfides, di-tert-dodecyl	68425-15-0	<= 100 %	H317



TPS™ 20

Oxirane	75-21-8	< 0.1 %	H220, H280, H301, H331, H314, H318, H372, H335, H350, H340, H360
---------	---------	---------	--

^{**}For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of necessary first-aid measures:

Inhalation:

If inhaled, remove victim to fresh air.

Skin

In case of contact, immediately flush skin with soap and plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eves

Immediately flush eye(s) with plenty of water.

Ingestion:

If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed:

For most important symptoms and effects (acute and delayed), see Section 2 (Hazard Statements and Supplemental Information if applicable) and Section 11 (Toxicology Information) of this SDS.

4.3. Indication of any immediate medical attention and special treatment needed:

Unless otherwise noted in Notes to Physician, no specific treatment noted; treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media (suitable):

Water spray, Carbon dioxide (CO2), Foam, Dry chemical

Extinguishing media (unsuitable):

A solid stream of water can cause frothing and spattering.

Protective equipment:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).



TPS™ 20

Further firefighting advice:

Do not permit water to enter containers.

Material may spatter or foam if contacted with water.

Fire fighting equipment should be thoroughly decontaminated after use.

Fire and explosion hazards:

When burned, the following hazardous products of combustion can occur:

Carbon oxides

Sulphur oxides

Hydrogen sulphide

Hazardous organic compounds

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, Emergency procedures, Methods and materials for containment/clean-up:

Prevent further leakage or spillage if you can do so without risk. Ventilate the area. Avoid generation of vapors. Contain and collect spillage with non-combustible absorbent material such as clean sand, earth, diatomaceous earth or non-acidic clay and place into suitable properly labeled containers for prompt disposal. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

Protective equipment:

Appropriate personal protective equipment is set forth in Section 8.

SECTION 7: HANDLING AND STORAGE

Handling

General information on handling:

Avoid breathing vapor or mist.

Avoid prolonged or repeated contact with skin.

Wash thoroughly after handling.

Emptied container retains vapor and product residue.

Observe all labeled safeguards until container is cleaned, reconditioned or destroyed.

Storage

General information on storage conditions:

Keep in a dry, cool place. Store in closed containers, in a secure area to prevent container damage and subsequent spillage.

Storage incompatibility - General:

Store separate from:

Acids

Strong oxidizing agents



TPS™ 20

hydrogen peroxide hypochlorites nitric acid

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Airborne Exposure Guidelines:

Oxirane (75-21-8)

US. ACGIH Threshold Limit Values

Time weighted average 1 ppm

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Reference:

Remarks: 29 CFR 1910.1047

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Short Term Exposure Limit (STEL): 5 ppm

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

OSHA Action level: 0.5 ppm

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Time weighted average 1 ppm

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions.

Engineering controls:

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits for: hydrogen sulfide, ethylene oxide. If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Respiratory protection:

Avoid breathing vapor or mist. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material

Product code: 001840 Version 3.0 Issued on: 12/09/2022 Page: 5 / 12



TPS™ 20

and/or its components. Full facepiece equipment is recommended and, if used, replaces need for face shield and/or chemical goggles. Consult OSHA Standard (29 CFR § 1910.1047 - Ethylene Oxide) to determine required type equipment for given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Skin protection:

Glove materials: Nitrile rubber

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Consult glove manufacturer to determine appropriate type glove material for given application. Wear chemical goggles, a face shield, and chemical resistant clothing such as a rubber apron when splashing may occur. Rinse immediately if skin is contaminated. Remove contaminated clothing immediately and wash before reuse. Clean protective equipment before reuse. Provide a safety shower at any location where skin contact can occur. Wash thoroughly after handling.

Eye protection:

Where eye contact may be likely, wear chemical goggles and have eye flushing equipment available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Color: colorless to light yellow

Physical state: liquid

Odor: Slightly acrid

Odor threshold: not determined

Flash point 291 °F (144 °C) (Method: closed cup)

Auto-ignition 464 °F (240 °C) (Method: Standard: A15)

temperature:

Lower flammable limit

(LFL):

Not determined

Upper flammable limit

(UFL):

Not determined

pH: not determined

Density: 950 kg/m3 (68 °F (20 °C))

Specific Gravity (Relative

density):

0.95 (68 °F(20 °C))Water=1 (liquid)

Bulk density: not determined

Product code: 001840 Version 3.0 Issued on: 12/09/2022 Page: 6 / 12

ARKEMA

TPS™ 20

Vapor pressure: 0.000 mmHg (68 °F (20 °C))(Method: OECD Test Guideline 104)

Boiling point/boiling

range:

379 °F (193 °C)

Melting point/range: -54 °F (-48 °C)

Freezing point: No data available.

Evaporation rate: not determined

Solubility in water: 0.26 μg/l 68 °F (20 °C) (Method: OECD Test Guideline 105)

Solubility in other solvents: [qualitative and

quantative]

Soluble in hydrocarbons

Viscosity, dynamic: 207.7 mPa.s 68 °F (20 °C)

53 mPa.s 104 °F (40 °C)

22 - 34 mPa.s 122 °F (50 °C)

% Volatiles: 100 %

Oil/water partition coefficient:

No data available.

Thermal decomposition: > 392 °F (> 200 °C)

Flammability: See GHS Classification in Section 2 if applicable

SECTION 10: STABILITY AND REACTIVITY

Stability

This material is chemically stable under normal and anticipated storage, handling and processing conditions.

Hazardous reactions:

None known.

Materials to avoid:

Acids

Strong oxidizing agents Hydrogen peroxide Hypochlorites Nitric acid

Conditions / hazards to avoid:

To avoid thermal decomposition, do not overheat.



TPS™ 20

Hazardous decomposition products:

Thermal decomposition giving flammable and toxic products: Carbon oxides sulfur oxides Hydrogen sulphide Hazardous organic compounds

SECTION 11: TOXICOLOGICAL INFORMATION

Data on this material and/or a similar material are summarized below.

Data for Polysulfides, di-tert-dodecyl (68425-15-0)

Acute toxicity

Oral:

No deaths occurred. (rat) LD0 > 2,500 mg/kg.

Dermal:

No deaths occurred. (rat) LD0 > 2,000 mg/kg.

Skin Irritation:

Causes mild skin irritation. (rabbit)

Eye Irritation:

Causes mild eye irritation. (rabbit)

Skin Sensitization:

Not a sensitizer. Guinea pig maximization test. No skin allergy was observed.

May cause an allergic skin reaction. LLNA: Local Lymph Node Assay. (mouse) Skin allergy was observed. Weak skin sensitizer

Repeated dose toxicity

Subchronic oral administration to rat / No adverse effects reported.

Genotoxicity

Assessment in Vitro:

No genetic changes were observed in laboratory tests using: bacteria, human cells

Genetic changes were observed in laboratory tests using: animal cells

Genotoxicity

Assessment in Vivo:

No genetic changes were observed in a laboratory test using: rats

Developmental toxicity



TPS™ 20

Exposure during pregnancy. Oral (rat) / No birth defects were observed. Exposure during pregnancy. Oral (rabbit) / No birth defects were observed.

SECTION 12: ECOLOGICAL INFORMATION

Chemical Fate and Pathway

Data on this material and/or a similar material are summarized below.

Data for Polysulfides, di-tert-dodecyl (68425-15-0)

Biodegradation:

Not readily biodegradable. (28 d) biodegradation 0 %

Bioaccumulation:

Does not bioaccumulate. 14 d (Cyprinus carpio (Carp))

Octanol Water Partition Coefficient:

log Pow: > 6.2, at 162 °F (72 °C) pH = 7

Ecotoxicology

Data on this material and/or a similar material are summarized below.

Data for Polysulfides, di-tert-dodecyl (68425-15-0)

Aquatic invertebrates:

No effect up to the limit of solubility. Daphnia (water flea) 48 h NOEC < 0.1 mg/l (Water accommodated fraction was tested.)

Algae:

No effect up to the limit of solubility. Pseudokirchneriella subcapitata (green algae) 72 h EL50 > 100 mg/l (Water accommodated fraction was tested.)

Microorganisms:

Growth inhibition / Pseudomonas putida 72 h NOEC = 10.000 mg/l

Chronic toxicity to fish:

No effect up to the limit of solubility Pimephales promelas (fathead minnow) 32 d NOEC > 0.00084 mg/l

Chronic toxicity to aquatic invertebrates:

No effect up to the limit of solubility Reproduction Test / Daphnia magna (Water flea) 21 d NOEC > 0.00079 mg/l

Chronic toxicity to aquatic plants:

No effect up to the limit of solubility. Growth inhibition / Pseudokirchneriella subcapitata (green algae) 72 d NOEC > 0.08 mg/l (Water accommodated fraction was tested.)

SECTION 13: DISPOSAL CONSIDERATIONS

Waste disposal:

Disposal via incineration is recommended. Dispose of in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in



TPS™ 20

waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

SECTION 14: TRANSPORT INFORMATION

US Department of Transportation (DOT): not regulated

International Maritime Dangerous Goods Code (IMDG): not regulated

SECTION 15: REGULATORY INFORMATION

<u>Chemical Inventory Status</u>		
US. Toxic Substances Control Act	TSCA	The components of this product are all on the Active TSCA Inventory.
Canadian Domestic Substances List (DSL)	DSL	All components of this product are on the Canadian DSL
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	All components of this product are listed or exempted
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	All components of this product are listed or exempted
Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	All components of this product are listed or exempted
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	All components of this product are listed or exempted
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	All components of this product are listed or exempted
Australian Inventory of Industrial Chemicals	AU AIICL	All components of this product are listed or exempted
Taiwan Chemical Substance Inventory (TCSI)	TCSI	All components of this product are listed

United States - Federal Regulations

SARA Title III - Section 302 Extremely Hazardous Chemicals:

Chemical name	CAS-No.	SARA	SARA Threshold
		Reportable	Planning Quantity
		Quantities	

or exempted



TPS™ 20

Oxirane 75-21-8 10 lbs 1000 lbs

SARA Title III - Section 311/312 Hazard Categories:

Acute Health Hazard

SARA Title III - Section 313 Toxic Chemicals:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):

<u>Chemical name</u> <u>CAS-No.</u> <u>Reportable quantity</u>

Oxirane 75-21-8 10 lbs

United States - State Regulations

California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

Chemical nameCAS-No.Oxirane75-21-8

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

 Chemical name
 CAS-No.

 Oxirane
 75-21-8

SECTION 16: OTHER INFORMATION



TPS™ 20

Full text of H-Statements referred to under sections 2 and 3.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eve damage.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

Latest Revision(s):

 Reference number:
 200005557

 Date of Revision:
 12/09/2022

 Date Printed:
 12/10/2022

TPS™ is a trademark of Arkema Inc.

All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Arkema Inc. ("Company") expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user's application(s). NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN. The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-management/medical-device-policy/ which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.